


2 GAS PIPING ISOMETRIC

NO SCAN



1 FIRST FLOOR PLAN - MECHANICAL


SCALE: 1/8"=1'-0"

H.V.A.C. ABBREVIATION LEGEND

A/C	AIR CONDITIONER	REV.	REVISION	A.H.U.	AIR HANDLING UNIT
DN.	DOWN	N.T.S.	NOT TO SCALE	D.G.	DOOR GRILLE
EXH.	EXHAUST	MFGR.	MANUFACTURER	F.I.D.	FIRE DAMPER
EXT.	EXTERIOR	R/A	RETURN AIR	DISP.	DISPOSABLE
E.F.	EXHAUST FAN	GR.	GRILLE	V.C.D.	VOLUME CONTROL DAMPER
A.F.F.	ABOVE FINISH FLOOR	C.D.	CEILING DIFFUSER	F/A	FRESH AIR
F.F.	FINISH FLOOR	REG.	REGISTER	S.P.	SAFE PAN
TYP.	TYPICAL	C.U.	CONDENSING UNIT	CD.	CONDENSATE DRAIN

HVAC SYMBOLS LEGEND

	THERMOSTAT, MTD +47" AFF
	EXHAUST FAN
	SECTION "A" - "A"
	REMOTE BULB SENSOR
	DUCT SMOKE DETECTOR
	TRANSITION
	TURNING VANE
	45° BRANCH DUCT TAKE-OFF
	FIRE DAMPER
	VOLUME CONTROL DAMPER
	RETURN REGISTER
	SUPPLY DIFFUSER
	RETURN AIR GRILLE
	SUPPLY REGISTER
	DUCTWORK TRANSITION
	ROOF MTD. EXH. FAN
	DUCT TURN DOWN
	DUCT TURN UP
	FLEXIBLE DUCT



2 SECTION 'A' - MECHANICAL

2 SCALE: 1/8"=1'-0"

OUTSIDE AIR CALCULATIONS

THE FOLLOWING IS BASED ON ASHRAE STANDARD 62.1-2012 FOR OUTSIDE AIR REQUIREMENTS

UNIT LABEL	OCCUPANCY CATALOG	AREA	ESTIMATED MAX. OCCUPANCY	PEOPLE + AREA CALC	EZ *	TOTAL
AHU #1	MEETING ROOM	515	50 PEOPLE PER 1,000 S.F./5 CFM PER PERSON	(26 X 5) + (515 X .06) = 161 PEOPLE AREA TOTAL		
AHU #1	MAIN ENTRY LOBBY	275	10 PEOPLE PER 1,000 S.F./5 CFM PER PERSON	(3 X 5) + (275 X .06) = 32 PEOPLE AREA TOTAL		
				AHU #1 TOTAL = 193	1.0	193/1.0 = 193
AHU #2	STORAGE	1990	0.12 CFM PER SQ. FT.	(N/A) + (1990 X .06) = 120 PEOPLE AREA TOTAL		
AHU #2	CORRIDOR	300	0.06 CFM PER SQ. FT.	(N/A) + (300 X .06) = 18 PEOPLE AREA TOTAL		
				AHU #2 TOTAL = 138	1.0	138/1.0 = 138
AHU #3	OFFICE	1150	5 PEOPLE PER 1,000 S.F./5 CFM PER PERSON	(6 X 5) + (1150 X .06) = 99 PEOPLE AREA TOTAL	1.0	99/1.0 = 99
AHU #4	HEALTH CLUB/WEIGHT RM.	1000	10 PEOPLE PER 1,000 S.F./20 CFM PER PERSON	(10 X 20) + (1000 X .06) = 269 PEOPLE AREA TOTAL		
AHU #4	LOCKER/DRESSING RM.	400	0.25 CFM PER SQ. FT.	(N/A) + (400 X .25) = 100 PEOPLE AREA TOTAL		
AHU #4	CORRIDOR	150	0.06 CFM PER SQ. FT.	(N/A) + (150 X .06) = 9 PEOPLE AREA TOTAL		
				AHU #4 TOTAL = 169	1.0	169/1.0 = 169
AHU #3	GYMNASIUM	7890	0.30 CFM PER SQ. FT.	(N/A) + (7890 X .06) = 2367 PEOPLE AREA TOTAL	1.0	2367/1.0 = 2367


* E_z (SYSTEM VENTILATION EFFICIENCY) AS PER 2012 NCMC TABLE 403.3.2.3

SUPPLY DIFFUSER SCHEDULE

- ① (2) 3"Ø VENT/INTAKE COMBUSTION AIR PIPES TO A CONCENTRIC VENT/INTAKE AIR TERMINATION KIT ON THE EXTERIOR WALL.
- ② PROVIDE VOLUME CONTROL DAMPER AND BACKDRAFT DAMPER PROVIDED IN OUTSIDE AIR DUCT AT THIS LOCATION. AIR FLOW TOWARDS AHU.
- ③ RETURN AIR DUCT PLENUM SHALL BE FULL SIZE OF AHU RETURN AIR OPENING.


SUPPLY DIFFUSER SCHEDULE				
A 100	DESIGNSATE LABEL FOR DIFFUSER TYPE		ALL DIFFUSERS ARE TO BE PROVIDED WITH OPPOSED BLADE DAMPERS UNLESS OTHERWISE SPECIFIED ON PLANS.	
	DESIGNSATE CFM QUANTITY FOR DIFFUSER			
LABEL	MANUFACTURER & MODEL NO.	NECK SIZE	CFM RANGE	REMARKS
A	TITUS TDC-AA	6"Ø	0 – 125	12X12 LOUVERED FACE
B	TITUS TDC-AA	6"Ø	0 – 125	24X24 LOUVERED FACE
C	TITUS TDC-AA	8"Ø	130 – 200	24X24 LOUVERED FACE
D	TITUS TDC-AA	10"Ø	205 – 325	24X24 LOUVERED FACE
E	TITUS TDC-AA	12"Ø	330 – 475	24X24 LOUVERED FACE
F	TITUS 300RL	14X6	205 – 300	SIDEWALL REGISTER

RETURN GRILLE SCHEDULE				
# 100	DESIGNSATE LABEL FOR GRILLE TYPE		FILTER SHALL BE PROVIDED AT UNIT.	
	DESIGNSATE CFM QUANTITY FOR GRILLE			
LABEL	MANUFACTURER & MODEL NO.	NECK SIZE	CFM RANGE	REMARKS
1	TITUS 355FL	10X10	0 - 400	LOUVER FACE
2	TITUS 355FL	24X24	1205 - 1450	LOUVER FACE
3	TITUS 50FF	24X48	2300 - 4000	EGGCRATE FACE
4	TITUS 50FF	14X18	0 - 1200	EGGCRATE FACE
5	TITUS 50FF	12X12	405 - 600	EGGCRATE FACE




1 **SECOND FLOOR PLAN - MECHANICAL**


SCALE: 1/8"=1'-0"




1 A/C MOUNTING DETAIL
NO SCALE



2 COND. UNIT MTG. DTL.
NO SCALE




2 COND. UNIT MTG. DTL.
NO SCALE




3 BRANCH DUCT DETAIL
NO SCALE

GENERAL GAS PIPING NOTES	
1. GAS PIPING AND FITTINGS SHALL BE SEAMLESS BLACK STEEL WITH MALLEABLE IRON FITTINGS. ELECTRICAL COUPLINGS OR FLANGES SHALL BE ELIMINATED. IF DISCERNABLE METAL IS CONNECTED, EXPOSED GAS PIPING AND ROOF SHALL BE PAINTED WITH A WHITE ALUMINUM PAINT. EXPOSED GAS PIPING ON BACK WALL SHALL BE "RUSTOLEUM" PAINTED TO MATCH BUILDING. GAS PIPING CONNECTIONS SHALL BE THREADED UNLESS OTHERWISE REQUIRED BY CODE.	
2. GAS PIPING SYSTEM SHALL BE INSTALLED TO THE REQUIREMENTS OF THE AGA PAMPHLET "INSTALLATION OF GAS APPLIANCES AND GAS PIPING" AND THE NFPA STANDARD #54. THE CONTRACTOR SHALL MAKE ALL ARRANGEMENTS AND PAY ALL FEES WITH THE "LOCAL" GAS COMPANY FOR THE INSTALLATION OF THE GAS METER, GAS SERVICE, AND ITS ACCESSORIES NECESSARY FOR THE USE OF GAS.	
3. GAS PIPING SHALL BE TESTED IN ACCORDANCE WITH THE PROCEDURES DESCRIBED IN NFPA #54, AND ANY OTHER TESTS REQUIRED BY THE LOCAL BUILDING DEPARTMENT AND/OR THE LOCAL GAS UTILITY COMPANY.	
4. THE PIPING SUBCONTRACTOR SHALL BE LICENSED BY THE STATE FOR THE INSTALLATION OF GAS PIPING.	
5. RUNOUT PIPING, FROM THE MAIN PIPING TO APPLIANCES, SHALL BE WITH AN INVERTED TRAP CONNECTION AT THE MAIN.	
6. A 12" DIRT LEG, AND A GAS COCK, SHALL BE PROVIDED AT ALL GAS APPLIANCES.	
7. ALL EXPOSED GAS PIPING SHALL BE IDENTIFIED BY A YELLOW LABEL MARKED "GAS" IN BLACK LETTERS. THE MARKERS SHALL BE AT INTERVALS NOT EXCEEDING 5'.	
8. ALL GAS BURNING EQUIPMENT SHALL BE INSTALLED PER NFPA #58, NFPA #54 (L.P.G.) OR NFPA #96 (COMMERCIAL COOKING EQUIPMENT).	
9. GAS PIPE SIZES 2-1/2" AND GREATER SHALL BE WELDED, IF REQUIRED BY CODE.	
10. GAS CONNECTIONS PER ANSI Z21.69	

GENERAL MECHANICAL NOTES	
1. THE CONTRACTOR SHALL FURNISH ALL LABOR, MATERIALS, AND EQUIPMENT NECESSARY FOR THE INSTALLATION OF A COMPLETE SYSTEM IN ACCORDANCE WITH THE CONTRACT DOCUMENTS, APPROVED PLANS, AND THE APPLICABLE STATE, COUNTY AND LOCAL ORDINANCES AND THE LATEST EDITION OF THE FOLLOWING PUBLICATIONS: SMACNA, ASHRAE, NFPA 90A, 90B, 91 & ANSI B-91. ALL DUCTWORK SHALL BE FABRICATED, INSTALLED, AND SUPPORTED AS PER SMACNA STANDARDS.	
2. THE CONTRACTOR SHALL PAY ALL COSTS OF INSPECTION, AND ALL OTHER COSTS INCIDENTAL TO THE COMPLETION AND TESTING OF THIS WORK.	
3. THE CONTRACTOR SHALL VISIT THE SITE AND COORDINATE WORK WITH OTHER TRADES TO INSURE ORDERLY AND PROFESSIONAL WORK.	
4. THE CONTRACTOR SHALL SUPPLY THE OWNER WITH ONE SET OF "AS-BUILT" DRAWINGS UPON COMPLETION OF THIS PROJECT. CONTRACTOR SHALL ALSO LEAVE FOR ONE AT LEAST ONE SET OF THE MANUFACTURER'S INSTALLATION AND OPERATIONS MANUALS FOR ALL EQUIPMENT PROVIDED ON THE PROJECT.	
5. ALL PROVIDED EQUIPMENT SHALL BE OF GOOD QUALITY. ALL WORK SHALL BE PERFORMED IN A WORKMANLIKE MANNER BY SKILLED WORKMAN.	
6. CONTRACTOR SHALL SUBMIT, FOR APPROVAL FIVE (5) COPIES OF MANUFACTURER'S DRAWINGS FOR EACH PIECE OF EQUIPMENT AND CONTROLS INCLUDED IN CONTRACT. IT IS STRONGLY PREFERRED THAT ALL DRAWINGS BE MADE IN THE FORM OF AN ELECTRONIC DRAWING ATTACHED IN A ZIP TYPE FORMAT.	
7. ALL SUPPLY AND RETURN AIR DUCTWORK SHALL BE GALVANIZED SHEET STEEL EXTERNALLY WRAPPED WITH A MIN. OF R5 INSULATION OR R8 IF DUCTWORK IS LOCATED EXTERIOR TO BLDG INSULATION ENVELOPE. ALL FLEX DUCT SHALL BE "THERMOFLEX" WITH A MINIMUM 42" DIA. APPROVED DUAL LAYER AND SHALL HAVE EQUIVALENT INSULATION.	
8. ALL EXHAUST DUCTS AND OUTSIDE AIR DUCTS SHALL BE GALVANIZED SHEET METAL WITH SEALED SEAMS AND JOINTS.	
9. DUCT DIMENSIONS ARE INSIDE DIMENSIONS.	
10. ALL AIR DUCTS (DIFUSERS, REGISTERS AND GRilles) SHALL BE ALL ALUMINUM CONSTRUCTION, PAINTED IN A SATIN OR WHITE ENAMEL FINISH OR AS SPECIFIED BY ARCHITECT. DEVICES SHALL BE TITAN, METALARE, AIRGUIDE. PROVIDE OPPOSED BLADE DAMPERS AT ALL DIFFUSERS AND REGISTERS.	
11. THERMOSTAT SHALL BE COMBINATION COOLING/HEATING, WITH SYSTEM "COOL-AUTO-HEAT-OFF" AND FAN "ON-AUTO" SELECTOR SWITCHES. PROVIDE PROGRAMMABLE TYPE THERMOSTAT. CONTRACTOR SHALL FULLY INSTRUCT OWNER ON HOW TO PROPERLY PROGRAM THERMOSTAT. PROGRAMMABLE THERMOSTAT SHALL BE PROVIDED BY MANUFACTURER OF INSTALLED AIR HANDLING UNIT. IT IS RECOMMENDED THAT DURING OCCUPIED HOURS, THE FAN BE SET TO "ON" IN LIEU OF "AUTO". * THERMOSTATS SHALL BE MOUNTED A MAX. OF 48" A.F.F.	
12. REFRIGERANT LINES SHALL BE COPPER, TYPE "L" HARD DRAWN WITH WROUGHT COPPER SOLDER JOINTS. FITTINGS USE 35/32 SOLDER. REFRIGERANT LINES SHALL BE SIZED AS PER MANUFACTURER'S RECOMMENDATIONS.	
13. SPLIT SYSTEMS (IF APPLICABLE) SHALL HAVE A MINIMUM OF 1-1/2" ARMAFLEX INSULATION (OR APPROVED EQUAL) USED FOR SUCTION LINES. INSTALLATION SHALL BE AS PER MANUFACTURER'S RECOMMENDATIONS.	
14. ALL BRANCH TAKE-OFFS TO BE PROVIDED W/MANUAL VOLUME DAMPERS AND TAPS AS PER PLANS REQUIREMENTS.	
15. PROVIDE NEW FILTERS FOR ALL AIR CONDITIONING EQUIPMENT BEFORE STARTING THEM. REPLACE THEM PRIOR TO FINAL ACCEPTANCE BY OWNER.	
16. PROVIDE MAKE-UP AIR DECKS WITH ACCESS TO ALL RETURN AIR DUCTS FOR FANS AND AHU'S. SERVICE BY COMMON DESIGN, SUPPLY OR RETURN DRAUM OF ABOVE 2000 CFM. ALL SMOKE DETECTORS SHALL BE BY ONE MANUFACTURER. COORDINATE VOLTAGE ETC. WITH ELECTRICAL CONTRACTOR AND FIRE ALARM SYSTEM BEFORE ORDERING. UPON DETECTION, SMOKE DETECTORS SHALL ASSISTED BY AUTOMATIC AIR MOVING EQUIPMENT AND ALL AIR MOVING EQUIPMENT SERVING THAT COMMON PLenum.	
17. HVAC CONTRACTOR SHALL PROVIDE A TEST AND BALANCE REPORT FOR ALL MECHANICAL EQUIPMENT, AIR DEVICES, DAMPERS, AHU'S AND FANS. THE T & B SHALL BE IN ACCORDANCE WITH THE AIR BALANCE COUNCIL STANDARDS, AND SHALL INCLUDE AIR QUALITY TESTS, AND SURVEYS. PROVIDE ONE AIR GRILLE FOR THE COOLING, LEAVING AND ENTERING AIR TEMPERATURE (T) FROM SUPPLY GRILLS AND EVAPORATORS.	
18. THERMOSTAT LOCATION SHALL BE APPROVED BY OWNER BEFORE INSTALLATION.	
19. ALL INSULATION SHALL HAVE FIRE/SMOKE RATING LESS THAN 25/50.	
20. MECHANICAL PLANS IN GENERAL, ARE DIAGRAMMATIC IN NATURE, AND ARE TO BE READ IN CONJUNCTION WITH ARCH. PLUMBING, ELECTRICAL AND STRUCTURAL PLANS AND SHALL BE CONSIDERED AS ONE SYSTEM. Duct and piping offset bends and transitions will be required to provide and install a complete functional system and shall be provided by the contractor at no additional cost to the owner.	
21. CONTRACTOR SHALL INSTALL ALL OUTDOOR EQUIPMENT TO WITHSTAND WIND LOADING FORCES AS REQUIRED BY LOCAL CODES. REFER TO STRUCTURAL PLANS BY OTHERS FOR STRUCTURAL DETAILS.	
22. PROVIDE ALL NECESSARY CONTACTORS, RELAYS, ETC., FOR A COMPLETE OPERATING SYSTEM.	
23. THROUGHOUT THE COURSE OF THE WORK, MINOR CHANGES AND ADJUSTMENTS TO THE PLANS AND SPECIFICATIONS MAY BE REQUESTED BY THE TENANT. THE CONTRACTOR SHALL MAKE SUCH ADJUSTMENTS WITHOUT ADDITIONAL COST TO THE TENANT, WHERE SUCH ADJUSTMENTS ARE NECESSARY FOR THE PROPER INSTALLATION AND OPERATION OF THE SYSTEMS, AND WITHIN THE SCOPE OF THE CONTRACT DOCUMENTS.	
24. NOTWITHSTANDING ANY OTHER PROVISIONS OF THE CONTRACT DOCUMENTS, THE CONTRACTOR BEARS ULTIMATE RESPONSIBILITY FOR COMPLIANCE OF THE INSTALLATION WITH THE REQUIREMENTS OF THE LOCAL AUTHORITY HAVING JURISDICTION.	
25. IF ANY ERRORS, DISCREPANCIES OR OMISSIONS APPEAR IN THE DRAWINGS, SPECIFICATIONS OR CONTRACT DOCUMENTS, THE CONTRACTOR SHALL BE RESPONSIBLE FOR WRITING OF SUCH ERROR OR OMISSION. IN THE EVENT OF THE CONTRACTOR FAILING TO GIVE SUCH NOTICE BEFORE CONSTRUCTION AND/OR FABRICATION OF THE WORK, HE WILL BE HELD RESPONSIBLE FOR THE RESULTS OF ANY SUCH ERRORS, DISCREPANCIES OR OMISSIONS AND THE COST OF RECTIFYING SAME.	



4 AIR HANDLING UNIT MOUNTING DETAIL
NO SCALE



5 AHU MOUNTING DETAIL
NO SCALE

FAN SCHEDULE										
LABEL	TYPE OF UNIT - AREA SERVED	MANUFACTURER & MODEL NO.	CFM	SP	MOUNTING ARRANGEMENT	MOTOR H.P.	ENCLOSURE TYPE	RPM	VOLTAGE	NOTES
EF-1 - 4	CABINET FAN - REFER TO PLANS	PENN ZEPHYR Z6	90	.125"	CEILING MOUNTED	50 WATTS	OPEN DRIP PROOF	1055	115V/1φ	1
EF-5 & 6	CABINET FAN - REFER TO PLANS	PENN ZEPHYR Z7	190	.125"	CEILING MOUNTED	68 WATTS	OPEN DRIP PROOF	1640	115V/1φ	1

NOTES: 1.) REFER TO ELECTRICAL PLANS FOR CONTROL.

CONDENSING UNIT				EVAPORATOR COIL UNIT				GAS FURNACE											
CU LABEL(S)	MANUFACTURER & MODEL NO.	TOTAL CAPACITY	SENSIBLE UNIT WEIGHT	COMP. RLA	FAN FLA	VOLTAGE	MOCP	EER/SEER	MANUFACTURER & MODEL NO.	TOTAL CFM	E.S.P.	BLOWER SPEED	FAN HP	VOLTAGE	INPUT BTUH	OUTPUT BTUH	FLUE SIZE	NOTES	
CU #1	CARRIER 24AHA460A005	57,200	42,970	275 LBS.	15.9	145	208V/3φ	35A	CARRIER CNPVP6124ALA (HORIZONTAL COIL)	AHU #1	CARRIER 59TP6A120E24--22	.40"	HIGH	1	120V/1φ	120,000	(2)3"Ø	1 THRU 4	
CU #2	CARRIER 24AHA460A005	57,200	42,970	275 LBS.	15.9	145	208V/3φ	35A	CARRIER CNPVP6124ALA (VERTICAL COIL)	AHU #2	CARRIER 59TP6A120E24--22	.40"	HIGH	1	120V/1φ	120,000	(2)3"Ø	1 THRU 4	
CU #3	CARRIER 24AHA448A005	45,190	33,990	243 LBS.	13.7	1.2	208V/3φ	30A	CARRIER CNPVP4821ALA (VERTICAL COIL)	AHU #3	CARRIER 59SP5A080E24--20	1,380	.40"	HIGH	1	120V/1φ	80,000	(2)3"Ø	1 THRU 4

GENERAL NOTES:

- * ALL RATINGS ARE AT ARI ENTERING CONDITIONS UNLESS OTHERWISE NOTED.
- * PROVIDE VIBRATION ISOLATION FOR UNITS.
- * EXTERNAL STATIC PRESSURE DOES NOT INCLUDE COIL OR FILTER PRESSURE DROP.
- * CONTRACTOR MAY SUBSTITUTE MANUFACTURER FOR APPROVED EQUAL. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY THAT ANY CLEARANCE REQUIREMENTS ARE MET FOR ANY SUBSTITUTIONS.

SPECIFIC NOTES:


- 1) SIZE AND RUN REFRIGERANT PIPING AS PER MANUFACTURER'S PUBLISHED RECOMMENDATIONS.
- 2) INSULATE REFRIGERANT SUCTION LINE WITH 2" ARMAFLEX OR APPROVED EQUAL.
- 3) PROVIDE 5 YEAR WARRANTY ON COMPRESSOR AND 1YEAR WARRANTY ON ALL PARTS AND LABOR.
- 4) FURNACE SHALL BE A 2-PIPE SYSTEM AND SHALL BE PROVIDED WITH CONCENTRIC VENT/INTAKE AIR ROOF TERMINATION KIT.

SYS. LABEL	MANUFACTURER	MODEL NO.	TOTAL CAPACITY	SENSIBLE CAPACITY	TOTAL CFM	O/A CFM	E.S.P.	FAN SPEED	COMP. RLA	OUTDOOR FAN FLA	INDOOR FAN HP	HEATER BTUH OUTPUT	VOLTAGE	MOCP	EER	NOTES	HEATER BTUH INPUT	UNIT WEIGHT
A/C #4	CARRIER	48TCEA07A25-0A0A0	75,210	58,110	2,400	SEE SCH.	.7"	1402	19.0	1.5	3.0	93,000	208V/3φ	50	11.0	1 THRU 12	115,000	896 LBS.
A/C #5,6	CARRIER	48TCFD14A35-0A0A0	148,670	105,370	5,000	SEE SCH.	.9"	1147	(1)3"Ø	6.2	5.0	205,000	208V/3φ	80	10.8	1 THRU 12	250,000	1525 LBS.

GENERAL NOTES:

- * ALL RATINGS ARE AT ARI ENTERING CONDITIONS UNLESS OTHERWISE NOTED.
- * EXTERNAL STATIC PRESSURE DOES NOT INCLUDE COIL OR FILTER PRESSURE DROP.
- * APPROVED EQUALS SHALL BE TRANE, LENNOX AND YORK. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY THAT ANY CLEARANCE REQUIREMENTS ARE MET FOR ANY SUBSTITUTIONS.

ABBREVIATION LEGEND:



* INSTALL AS PER MANUFACTURER'S RECOMMENDATIONS AT: <http://www.ductsox.com>

2 DUCTSOX MOUNTING DETAILS

VERONA DUCTSOX SPECIFICATIONS

PART 1—GENERAL

1.01 DESCRIPTION OF WORK:

A. Extent of non-metal ductwork is indicated on drawings and by requirements of this section.

B. Types of non-metal ductwork required for this project include the following:

1. Fabric Air Dispersion Products.

1.02 QUALITY ASSURANCE:

A. Building Codes and Standards:

1. Product must be Classified by Underwriters Laboratories in accordance with the 25/50 flame spread / smoke developed requirements of NFPA 90-A and are also classified in accordance with ICC Evaluation Service AC167 and UL 2518. Product must meet UL-C (Canada), BS 5867, part 2, 1980 and GB8624-2006 8-s1, d0, t1 level.

2. All product sections must be labeled with the logo and classification marking of Underwriters Laboratories.

B. Design and Quality Control:

1. Manufacturers must have documented design support information including duct sizing, vent and orifice location, vent and orifice sizing, length, and suspension. Parameters for design, including maximum air temperature, velocity, pressure and fabric permeability, shall be considered and documented.

1.03 SUBMITTALS:

A. Product Data: Submit manufacturer's specifications on materials and manufactured products used for work of this section.

B. Design Code Data: Submit UL file number under which product is Classified by Underwriter's Laboratories NFPA 90, ICC AC167 and UL 2518.

1.04 WARRANTY:

A. Manufacturer must provide a 5 Year Product Warranty for products supplied for the fabric portion of this system as well as a Design and Performance Warranty.

1.05 DELIVERY, STORAGE AND HANDLING:

A. Protect fabric dispersion systems from damage during shipping, storage and handling.

B. Where possible, store products inside and protect from weather. Where necessary to store outside, store above grade and enclose with a vented waterproof wrapping.

PART 2 — PRODUCTS

2.01 MANUFACTURER:

Subject to compliance with requirements, choose one of the following:

A. Ductsox Corporation

Phone: (866) DUCTSOX or (563) 589-2777

FAX: (866) 398-1646 or (563) 589-2754

www.Ductsox.com

2.02 FABRIC AIR DISPERSION SYSTEM:

A. Verona Fabric: Air diffusers shall be constructed of a woven fire retardant fabric complying with the following physical characteristics:

1. Fabric Construction: 100% Flame Retardant

2. Weight: 6.2 oz. /yd² per ASTM D3776

3. Color: (MUST SPECIFY—red, white, blue, green, gray, tan or black)

4. Fabric Porosity: 2 (+/-1) cfm/ft² per ASTM D737, Frazier. Custom Porosity

5. Temperature Range: 0 degrees F to 180 degrees F

6. Fire Retardancy: Classified by Underwriters Laboratories in accordance with the requirements of NFPA 90-A and AC-167 (noted above).

B. SYSTEMS FABRICATION REQUIREMENTS:

1. Air dispersion accomplished by linear vent and permeable fabric. Linear vents must be sized in 1 CFM per linear foot increments (based on .5SP), starting a 1 CFM through 90 CFM per linear foot. Linear vent is to consist of an array of open orifices rather than a mesh style vent or a mesh style vent. Linear vents should be designed to minimize dusting on fabric surface.
2. Size and location of linear vents to be specified and approved by manufacturer.
3. Inlet connection to metal duct via fabric draw band with anchor patches as supplied by manufacturer. Anchor patches to be secured to metal duct via zip screw fastener supplied by contractor.

4. Inlet connection includes zipper for easy removal / maintenance.
5. Lengths to include required zippers as specified by manufacturer.

6. System to include adjustable Flow Device to balance turbulence, airflow and distribution as required. Flow distribution device shall include ability to adjust the airflow resistance from 0.60 in w.g. static pressure.
7. Fabric system shall include connectors to accommodate suspension system listed below.
8. Any deviation from a straight run shall be made using a gored elbow or an efficiency tee. Normal 90 degree elbows are 5 gores and the radius of the elbow is 1.5 times the diameter of the Ductsox.

C. DESIGN PARAMETERS:

1. Fabric air diffusers shall be designed from 0.25" water gage minimum to 3.0" maximum, with 0.5" as the standard.
2. Fabric air diffusers shall be limited to design temperatures between 0 degrees F and 180 degrees F (-17.8 degrees C and 82 degrees C).
3. Design CFM, static pressure and diffuser length shall be designed or approved by the manufacturer.

4. Do not use fabric diffusers in concealed locations.
5. Use fabric diffusers only for positive pressure air distribution components of the mechanical ventilation system.

D. SUSPENSION HARDWARE: (include applicable components only)

1. Tension Cable: System shall be installed using a tension cable system including a single (1 Row) or double strands (2 Row) of cable located 3" above top-dead-center (1 Row) or 3" above the 10 and 2 o'clock locations of the Ductsox system. 2 Row supports are required for systems of 32" diameter and larger. Hardware to include cable, eye bolts, thimbles, cable clamps and turnbuckle(s) as required. System attachment shall be made using nylon cable clips spaced 24" inches.

Component options include: (must specify per area if multiple on same project):

- a. Galvanized Steel Cable
- b. Stainless Steel Cable
- c. Plastic Coated Stainless Steel Cable
- d. Adjustable Grapple Mid-Supports Available lengths: 5", 10", 15", 20" and 30"

E. 3x1 Suspension: (Available for duct diameters from 10" to 48") System shall include a 3

- Row connection to fabric system at 10, 12, and 2 o'clock locations. The powder-coated aluminum hangers are secured and connected to a single (1 Row) tension cable every 3'-0" and connect to the fabric system at the 10 and 2 o'clock locations with detachable D-Clasps. The fabric system will also have intermediate cable clips located at 12 o'clock and between the hangers to attach directly to the single tension cable system located 3" above top-dead-center location of the fabric system. Tension cable hardware to include cable, eye bolts, thimbles, cable clamps, and turnbuckle(s) as required.

Component options include:

- a. Galvanized Steel Cable
- b. Stainless Steel Cable
- c. Adjustable Grapple Mid-Supports Available lengths: 5", 10", 15", 20" and 30"

3. 4x2 Suspension: (Available for duct diameters from 50" to 60") System shall include a 4 Row connection to fabric system at 10, 11, 1 and 2 o'clock locations. The powder-coated aluminum hangers are secured and connected to a double (2 Row) tension cable every 3'-0" and connect to the fabric system at the 10 and 2 o'clock locations with detachable D-Clasps. The fabric system will also have intermediate cable clips located at 11 and 2 o'clock and between the hangers to attach directly to the double tension cable system located 1" above top-dead-center location of the fabric system. Tension cable hardware to include cable, eye bolts, thimbles, cable clamps, and turnbuckles as required.

Component options include:

- a. Galvanized Steel Cable
- b. Stainless Steel Cable
- c. Adjustable Grapple Mid-Supports Available lengths: 5", 10", 15", 20" and 30"

4. Suspended H-Track: System shall include a single (1 Row) or double (2 Row) runs of aluminum H-track system located 1.5 above top-dead-center (1 Row) or 1.5 above the 10 and 2 o'clock (2 Row) locations of Ductsox system. 2 Row supports are required for systems of 32" diameter and larger. Hardware to include 10" sections of track, track connectors, track end caps and vertical cable support kits consisting of a length of cable with a locking stud end and Grapple quick cable connectors. Radius aluminum track must be included for all radius sections.

Component / Track attachment

- a. Cord in continuous supporting cord (not suggested for systems >24" Dia.)
- b. Track tabs are a detachable tab positioned every 24" along the length of the system (all diameters).

Hardware components (optional)

- a. Provide 316 Stainless Steel components including coupler assembly, vertical cable support and Grapple quick cable connector.

5. 3x1 H-Track Suspension: (Available for duct diameters from 10" to 48") System shall consist of a 3x1 hanger used in conjunction with an H-track suspension system. System shall include a 3 Row connection to fabric system at 10, 12, and 2 o'clock locations. The powder-coated aluminum hangers are secured and connected to a single (1 Row) aluminum H-track every 3'-0" and connect to the fabric system at the 10 and 2 o'clock locations with detachable D-Clasps. The fabric system will also have intermediate track tabs located at 12 o'clock and between the hangers to attach directly to the H-track suspension system located 1.5" above top-dead-center location of the fabric system. Hardware to include 10" sections of track, splice connectors, track end caps and vertical cable support kits consisting of a length of cable with a locking stud end and Grapple quick cable connectors. Radius aluminum track must be included for all radius sections.

Component / Track attachment

- a. Cord in continuous supporting cord (not suggested for systems >24" Dia.)
- b. Track tabs are a detachable sliding tab positioned every 24" along the length of the system (all diameters).

6. 4x2 H-Track Suspension: (Available for duct diameters from 50" to 60") System shall consist of a 4x2 hanger used in conjunction with an H-track suspension system. System shall include a 4 Row connection to fabric system at 10, 11, 1 and 2 o'clock locations. The powder-coated aluminum hangers are secured and connected to a double (2 Row) aluminum H-track every 3'-0" and connect to the fabric system at the 10 and 2 o'clock locations with detachable D-Clasps. The fabric system will also have intermediate track tabs located at 11 and 2 o'clock and between the hangers to attach directly to the H-track suspension system located 1.5" above top-dead-center location of the fabric system. Hardware to include 10" sections of track, splice connectors, track end caps and vertical cable support kits consisting of a length of cable with a locking stud end and Grapple quick cable connectors. Radius aluminum track must be included for all radius sections.


Component / Track attachment

- a. Cord in continuous supporting cord (not suggested for systems >24" Dia.)
- b. Track tabs are a detachable sliding tab positioned every 24" along the length of the system (all diameters).

7. Flush-Mount Track: System shall include aluminum Flush-Mount system located 1.5" above top-dead-center of Ductsox system. Hardware to include 12" section of track, track tabs, splice connections and end caps as required. Track tabs must promote easy sliding movement through aluminum track and must be detachable from the fabric. Radius aluminum track for support of the elbows through the corners using either Track tabs or Cord-In.

Fabric / Track attachment

- a. Cord in continuous supporting cord (not suggested for systems >24" Dia.)
- b. Track tabs are a detachable sliding tab positioned every 24" along the length of the system (all diameters).



1 PART. SECOND FLOOR PLAN - MECHANICAL


SCALE: 1/8"=1'-0"


PLUMBING ABBREVIATION LEGEND			
DN.	DOWN	C.C.	CENTER TO CENTER
EXT.	EXTERIOR	N.T.S.	NOT TO SCALE
F.D.	FLOOR DRAIN	M.F.G.R.	MANUFACTURER
F.F.	FINISH FLOOR	S.O.V.	SHUT OFF VALVE
A.F.F.	ABOVE FINISH FLOOR	W.C.	WATER CLOSET
V.F.R.	VENTURE ROOF	LAV.	LAVATORY
TYP.	TYPICAL	S.K.	SINK
R.D.	ROOF DRAIN	D.W.	DISH WASHER
REV.	REVISION	E.D.F.	ELECTRIC DRINKING FOUNTAIN
O.C.	ON CENTER	U.R.	URINAL

SPECIFIC PLUMBING NOTES		
①	CONNECT TO EXISTING SANITARY PIPING BELOW GRADE IN THIS AREA. CONTRACTOR SHALL VERIFY EXACT LOCATION PRIOR TO CONSTRUCTION.	

NOTE: THIS IS AN EXISTING FACILITY WHICH HAS EXISTING SANITARY AND WATER DISTRIBUTION SYSTEMS. ALTERATIONS TO EXISTING WORK BEING OF SUCH NATURE THAT ALL FACETS OF THE WORK ARE IMPOSSIBLE TO DETAIL AND SPECIFY. IT IS THEREFORE THE RESPONSIBILITY OF THE CONTRACTOR TO CALL FOR EXISTING SYSTEMS AND MAKE HIMSELF FAMILIAR WITH THE CONDITIONS AND RELATE THESE CONDITIONS TO THE SCOPE OF THE PROPOSED NEW WORK. ALL BIDS ARE EXPECTED TO ENCOMPASS THE TOTAL WORK SCOPE NEEDED TO PLACE THE COMPLETED SYSTEM IN WORKING CONDITION.

PLUMBING SYMBOLS LEGEND	
○	FLOOR DRAIN
○○	HOSE BIBB
—○—	CLEANOUT
—○—	RELIEF VALVE
—○—	AIR CHAMBER
—○—	UNION
—○—	SOIL OR WASTE LINE
—○—	SANITARY VENT LINE
—○—	DOMESTIC COLD WATER
—○—	DOMESTIC HOT WATER
—○—	DOMESTIC WATER RECIRCULATION
—○—	PRESSURE & TEMP. RELIEF LINE
—○—	CONDENSATE DRAIN LINE
—○—	RAIN WATER LEADER
—○—	GAS LINE
—○—	SAFEWASTE LINE
—○—	FIRE PROTECTION
—○—	SHUT OFF VALVE
—○—	SAFEPLAN LINE
○	FIRE SPRINKLER HEAD
—○—	PIPE TURN UP
—○—	PIPE TURN DOWN
—○—	P-TRAP







(WATER PIPING)

1 FIRST FLOOR PLAN - PLUMBING

SCALE: 1/8"=1'-0"



1 CONDENSATE P-TRAP DETAIL

NOT TO SCALE

2 DRYWELL DETAIL

NO SCALE

3 WATER HEATER DETAIL

NO SCALE

GENERAL PLUMBING NOTES	
1.) DRAWINGS ARE DIAGRAMMATIC AND SHALL NOT BE SCALED. REFER TO ARCHITECTURAL PLANS AND ELEVATIONS FOR EXACT LOCATION OF ALL PLUMBING FIXTURES, EQUIPMENT, ETC.. PLUMBING CONTRACTOR SHALL FURNISH AND INSTALL ALL ITEMS REQUIRED FOR A COMPLETE AND ACCEPTABLE WORKING INSTALLATION. CONTRACTOR IS RESPONSIBLE TO INSTALL ALL FIXTURES AND EQUIPMENT IN STRICT CONFORMITY WITH MANUFACTURER'S INSTALLATION INSTRUCTIONS. THIS REQUIREMENT IS TO SUPERSEDE ANY DETAILS OR INFORMATION CONTAINED ON THESE DRAWINGS.	
2.) ALL WORK AND MATERIALS SHALL COMPLY WITH THE LATEST EDITION OF THE NATIONAL, STATE, AND ALL LOCAL CODES AND ORDINANCES HAVING JURISDICTION.	
3.) THE PLUMBING CONTRACTOR SHALL VISIT THE SITE AND THOROUGHLY FAMILIARIZE HIMSELF WITH ALL EXISTING CONDITIONS. ALL EXECUTION AND BACKFILL AS REQUIRED FOR THIS PHASE OF CONSTRUCTION SHALL BE A PART OF THIS CONTRACT.	
4.) ALL MATERIAL SHALL BE NEW.	
5.) ALL WORK SHALL BE PERFORMED BY A LICENSED PLUMBING CONTRACTOR IN A FIRST CLASS WORKMANLIKE MANNER. THE COMPLETED SYSTEM SHALL BE FULLY OPERATIVE AND ACCEPTED BY ENGINEER/ARCHITECT.	
6.) ALL REQUIRED INSURANCE SHALL BE PROVIDED FOR PROTECTION AGAINST PUBLIC LIABILITY OR PROPERTY DAMAGE FOR THE DURATION OF THE WORK.	
7.) THE PLUMBING CONTRACTOR SHALL SECURE AND PAY ALL PERMIT FEES, INSPECTIONS, AND TESTS.	
8.) ALL WORK SHALL BE COORDINATED WITH OTHER TRADES TO AVOID INTERFERENCE WITH THE PROGRESS OF CONSTRUCTION.	
9.) THE PLUMBING CONTRACTOR SHALL GUARANTEE ALL MATERIALS AND WORKMANSHIP FREE FROM DEFECTS FOR A PERIOD OF NOT LESS THAN (1) ONE YEAR FROM DATE OF ACCEPTANCE. CORRECTION OF ANY DEFECTS SHALL BE COMPLETED WITHOUT ADDITIONAL CHARGE AND SHALL INCLUDE REPLACEMENT OR REPAIR OF ANY OTHER PHASE OF THE INSTALLATION WHICH MAY HAVE BEEN DAMAGED THEREBY.	
10.) VERIFY LOCATION, SIZE AND INVERTS OF ALL EXISTING UTILITIES PRIOR TO START OF CONSTRUCTION. ADVISE ARCHITECT/ENGINEER OF ANY DISCREPANCIES.	
11.) ALL FIXTURES SHALL BE PROVIDED WITH READILY ACCESSIBLE STOPS.	
12.) ALL BELOW FLOOR SLAB WATER PIPING SHALL BE FLEXIBLE "TEMPIRE PEX (CROSS-LINKED POLYETHYLENE)" INSTALLED AS PER MANUFACTURERS RECOMMENDATIONS FOUND HERE: WWW.LUBRIZOL.COM . ALL ABOVE SLAB WATER PIPING SHALL BE PVC, APPROVED AS PVC, IF APPROVED BY LOCAL AUTHORITIES HAVING JURISDICTION, OTHERWISE CAST IRON. PVC SHALL NOT BE INSTALLED IN A/C RETURN AIR PLenum OR PENETRATE FIRE RATED WALLS OR FLOORS.	
13.) SOIL, WASTES AND VENT PIPING SHALL BE PVC #40 DMV. WASTE AND VENT PIPING ABOVE SLAB SHALL BE PVC, IF APPROVED BY LOCAL AUTHORITIES HAVING JURISDICTION, OTHERWISE CAST IRON. PVC SHALL NOT BE INSTALLED IN A/C RETURN AIR PLenum OR PENETRATE FIRE RATED WALLS OR FLOORS.	
14.) AIR CONDITIONING CONDENSATE DRAIN PIPING SHALL BE PVC #40 OR COPPER DRAIN WASTE AND BENT PIPE AND FITTINGS. INSULATE ALL CONDENSATE PIPING EXCEPT EXTERIOR PIPING. INSTALL ALL CONDENSATE PIPING FOR AIR CONDITIONING UNITS AS REQUIRED PER LOCAL CODES.	
15.) FURNISH AND INSTALL APPROVED WATER HAMMER ARRESTORS AT EACH GROUP OF FIXTURES. INSTALLATION OF WATER HAMMER ARRESTORS SHALL CONFORM TO THE MANUFACTURER'S RECOMMENDATIONS. PROVIDE AND INSTALL AN APPROVED WATER HAMMER ARRESTOR AT EACH FIXTURE OR DEVICE THAT HAS A SOLENOID WATER CONTROL VALVE.	
16.) PROVIDE CHROME PLATED COMBINATION COVERED PLATE AND CLEANOUT PLUG FOR ALL WALL CLEANOUTS, JOSAM 58890.	
17.) INSULATE LINES AS FOLLOWS:	
A.) 1-1/2" THICK ARMAFLEX PREFORMED INSULATION SHALL BE PROVIDED ON BOTH C.W. & H.W. WHEN PIPING IS LOCATED OUTSIDE OF THE INSULATED BUILDING ENVELOPE.	
B.) 1-1/2" THICK ARMAFLEX PREFORMED INSULATION SHALL BE PROVIDED ON H.W. PIPING & H.W. RECIRC. PIPING, ONLY WHEN THERE IS A H.W. RECIRCULATING PIPING SYSTEM.	
C.) CONDENSATE PIPING: 1/2" THICK ARMAFLEX PREFORMED OR APPROVED EQUAL.	


PLUMBING FIXTURE SCHEDULE	
P-1 (FLOOR MOUNTED FLUSH TANK WATER CLOSET)	
SHALL BE AN AMERICAN STANDARD MODEL 2704A-001 CADET 3 ELONGATED 1.6 GPF TOILET, VITREOUS CHINA, CADET FLUSHING SYSTEM, TANK TYPE, FLOOR MOUNTED, FLOOR OUTLET, WITH AMERICAN STANDARD OPEN FRONT HEAVY-DUTY COMMERCIAL SEAT MODEL 5901.100. WATER CLOSET: https://goo.gl/r2TofA TOILET SEAT: https://goo.gl/120eyk	
P-2 (HANDICAPPED FLOOR MOUNTED FLUSH TANK WATER CLOSET)	
SHALL BE AN AMERICAN STANDARD MODEL 2704A-001 CADET 3 RIGHT HEIGHT ELONGATED 1.6 GPF TOILET, VITREOUS CHINA, CADET FLUSHING SYSTEM, TANK TYPE, FLOOR MOUNTED, FLOOR OUTLET, WITH AMERICAN STANDARD OPEN FRONT HEAVY-DUTY COMMERCIAL SEAT MODEL 5901.100. * TOILET LEVER HANDLE SHALL BE LOCATED ON ACCESSIBLE SIDE OF TOILET. WATER CLOSET: https://goo.gl/xP4isI TOILET SEAT: https://goo.gl/120eyk	
P-3 (HANDICAPPED URINAL AND FLUSH VALVE)	
SHALL BE AN AMERICAN STANDARD WASHBROOK MODEL 6501.511 3/4" TOP SPUD. 0.125 TO 1.0 GPF, URINAL INCLUDES AMERICAN STANDARD MANUAL FLUSH VALVE MODEL 6590.001 3/4" TOP SPUD. URINAL & VALVE: https://goo.gl/y1Staf	
P-4 (HANDICAPPED WALL HUNG LAVATORY)	
SHALL BE AN AMERICAN STANDARD REGALYN LAVATORY MODEL 4869.004 (CENTER HOLE ONLY), VITREOUS CHINA, WALL MOUNT WITH CONCEALED ARMS SUPPORT. FAUCET SHALL BE A "CHICAGO" MODEL 333-665PRA/BP METERING FAUCET, UNIT IS ADA COMPLIANT, ADJUSTABLE RUN TIME FROM 2 TO 15 SECONDS, OPENS WITH PUSH, 0.20 MAX GALLON/CYCLE. WATER PIPING AND P-TRAP SHALL BE COVERED WITH AN UNDER-SINK PROTECTIVE PIPE COVER KIT BY TRUEBRO (HTTP://WWW.TRUEBRO.COM) OR APPROVED EQUAL. LAVATORY: https://goo.gl/LLwx4I FAUCET: https://goo.gl/69Dj0w	
P-5 (HANDICAPPED COUNTER TOP LAVATORY)	
SHALL BE AN AMERICAN STANDARD REGALYN MODEL 0491.019 VITREOUS CHINA SELF-FILLING. FAUCET SHALL BE A "CHICAGO" MODEL 333-665PRA/BP METERING FAUCET, UNIT IS ADA COMPLIANT, ADJUSTABLE RUN TIME FROM 2 TO 15 SECONDS. OPENS WITH PUSH, 0.20 MAX GALLON/CYCLE. WATER PIPING AND P-TRAP SHALL BE COVERED WITH AN UNDER-SINK PROTECTIVE PIPE COVER KIT BY TRUEBRO (HTTP://WWW.TRUEBRO.COM) OR APPROVED EQUAL. LAVATORY: https://goo.gl/S5bYhx FAUCET: https://goo.gl/69Dj0w	
P-6 (WALL HUNG LAVATORY)	
SHALL BE AN AMERICAN STANDARD REGALYN MODEL 4869.004 (CENTER HOLE ONLY), VITREOUS CHINA, WALL MOUNT WITH CONCEALED ARMS SUPPORT. FAUCET SHALL BE A "CHICAGO" MODEL 333-665PRA/BP METERING FAUCET, UNIT IS ADA COMPLIANT, ADJUSTABLE RUN TIME FROM 2 TO 15 SECONDS, OPENS WITH PUSH, 0.20 MAX GALLON/CYCLE. LAVATORY: https://goo.gl/LLwx4I FAUCET: https://goo.gl/69Dj0w	
P-7 (HANDICAPPED H/L/O ELECTRIC WATER COOLER COMBINATION & WALL BRACKET)	
SHALL BE AN "OASIS" MODEL PGFBACSL, SPLIT LEVEL TWO STATION WATER COOLER WITH BARRIER FREE ACCESS. BI-LEVEL VERSACOOLER II WITH VERSAFILTER. 8.0 GPM, 4.4 FLA, 115V/10A WATER COOLER: https://goo.gl/xnEra3	
P-8 (HANDICAPPED H/L/O ELECTRIC WATER COOLER COMB. W/BOTTLE FILLER & WALL BRACKET)	
SHALL BE AN "OASIS" MODEL PGFBEBFSL, SPLIT LEVEL TWO STATION WATER COOLER WITH BARRIER FREE ACCESS. BI-LEVEL VERSACOOLER II WITH VERSAFILTER & HANDS FREE VERSAFILTER. 8.0 GPM, 4.4 FLA, 115V/10A WATER COOLER: https://goo.gl/0c0Wmf	
P-9 (FLOOR MOUNTED UTILITY SINK)	
SHALL BE A FLORESTON #36X36X6" MOLDED MOP BASIN WITH 3" OUTLET. PROVIDE WITH MR-370 MOP HANGER, BLOC WITH WALL BRACE, PAIL RACK AND APPROVED VACUUM BREAKER, MR-370 HOSE & HOSE BRACKET, MR-372 MOP HANGER, MR-373 BUMPER GUARDS AND MR-377 STAINLESS STEEL WALL GUARD. SINK: https://goo.gl/Nn75Y FAUCET/ACCESSORIES: https://goo.gl/wcWfM7	
P-10 (WALL MOUNT UTILITY SINK)	
SHALL BE AN "AMERICAN STANDARD" LAKEWELL SERVICE SINK MODEL 7692.008, ENAMELED CAST IRON AND RIM GUARD. FAUCET SHALL BE AN "AMERICAN STANDARD" MODEL 8351.076 EXPOSED YOKE WALL-MOUNT UTILITY FAUCET W/VACUUM BREAKER. SINK: https://goo.gl/79Ujt FAUCET: https://goo.gl/TMfzmq	
NOTES:	
1.) ALL PLUMBING FIXTURES SHALL BE AS SPECIFIED OR APPROVED EQUAL.	
2.) PROVIDE ANGLE STOPS ON ALL WATER SERVICE LINES TO FIXTURES FOR INDIVIDUAL SHUT-OFF.	

P-4


ELECTRICAL SYMBOLS LEGEND		NOTE: NOT ALL SYMBOLS MAY BE USED ON PROJECT	
SYMBOLS	DESCRIPTION	SYMBOLS	DESCRIPTION
	DUPLEX RECEPTACLE, MTD. +18" AFF		TRANSFORMER - SIZE AS NOTED
	240 VOLT RECEPTACLE (HT. AS REQ.)		PANEL - SIZE AS NOTED
	QUADRUPLEX RECEPTACLE, MTD. +18"		MOMENTARY CONTACT PUSH BUTTON
	COUNTERTOP HT. RECEPTACLE +42"		F-FAN; M-MOTOR; P-PUMP
	SINGLE POLE SWITCH, MTD. +47"		SPECIAL OUTLET - AS REQUIRED
	THREE-WAY SWITCH, MTD. +47"		CKT. HOMERUN (B INDICATES PANEL)
	MANUAL STARTER SWITCH		2" DESIGNATES CIRCUIT NUMBER
	DIMMER SWITCH, MTD. +47"		EXIT SIGN ONE SIDED, OR TWO SIDED
	SWITCH W/ ILLUM WHEN ON MTD. +47"		EMERGENCY LIGHTING
	THREE-WAY SWITCH W/ OCCU SENSOR MTD. +47"		RECESSED MOUNTED LIGHTING FIXTURE
	SWITCH W/ OCCU SENSOR MTD. +47"		B DESIGNATES FIXTURE TYPE
	JUNCTION BOX, FLUSH IF POSSIBLE		HIGHBAY HID LIGHTING FIXTURE
	TELEPHONE / DATA OUTLET +18"		B DESIGNATES FIXTURE TYPE
	DED. COMPUTER TERM. OUTLET +18"		HIGHBAY HID LIGHTING FIXTURE
	DISCONNECT SWITCH W/ STARTER		B DESIGNATES FIXTURE TYPE
	DISCONNECT SWITCH		FLUORESCENT STRIP LIGHTING FIXTURE
	FLR. MTD. FLUSH DUPLEX RECEPTACLE		B DESIGNATES FIXTURE TYPE
	FLR. MTD. FLUSH QUAD. RECEPTACLE		FLUORESCENT STRIP LIGHTING FIXTURE
	FLR. MTD. FLUSH PHONE/DATA OUTLET		B DESIGNATES FIXTURE TYPE
	FLR. MTD. FLUSH COMPUTER OUTLET		FLUORESCENT STRIP LIGHTING FIXTURE
	AREA SMOKE DETECTOR		B DESIGNATES FIXTURE TYPE
	HEAT DETECTOR		LED LIGHTING FIXTURE
	DUCT SMOKE DETECTOR		B DESIGNATES FIXTURE TYPE
	FIRE ALARM MAN. PULL STATION +47"		ISOLATED GROUND
	HORN WITH STROBE LIGHT, MTD. +80'		
	# BESIDE DEVICE IS CANDLESTICK RATING		
	STROBE LIGHT ONLY, MTD. +80'		
	# BESIDE DEVICE IS CANDLESTICK RATING		
L30		FAAP	FIRE ALARM ANNUNCIATOR PANEL
L40		FAAP	FIRE ALARM ANNUNCIATOR PANEL


ELECTRICAL SYSTEM AND EQUIPMENT	
METHOD OF COMPLIANCE	
PRESCRIPTIVE <input checked="" type="checkbox"/>	PERFORMANCE <input type="checkbox"/>
ENERGY COST BUDGET <input type="checkbox"/>	
PROVIDE A STANDARD RISER DIAGRAM WHICH INDICATES DESIGNATED POINTS FOR CHECK METERING. PROVIDE A STANDARD PANEL SCHEDULE DESCRIPTION WHICH IDENTIFIES DIFFERENT ENDUSE LOADS.	
LIGHTING SCHEDULE	
LAMP TYPE REQUIRED IN FIXTURE SEE SCHEDULE ON DRAWINGS NUMBER OF LAMPS IN FIXTURE SEE SCHEDULE ON DRAWINGS BALLAST TYPE USED IN FIXTURE SEE SCHEDULE ON DRAWINGS NUMBER OF PHASES SEE SCHEDULE ON DRAWINGS TOTAL WATTAGE PER FIXTURE SEE SCHEDULE ON DRAWINGS TOTAL INTERIOR WATTAGE SPECIFIED VS ALLOWED 7140.00 VS 15496.19 TOTAL EXTERIOR WATTAGE SPECIFIED VS ALLOWED N/A	
EQUIPMENT SCHEDULES WITH MOTORS (NOT USED FOR MECHANICAL SYSTEMS)	
MOTOR HORSEPOWER N/A NUMBER OF PHASES N/A MINIMUM EFFICIENCY N/A MOTOR TYPE N/A NUMBER OF POLES N/A	
DESIGNER STATEMENT:	
TO THE BEST OF MY KNOWLEDGE AND BELIEF, THE DESIGN OF THIS BUILDING COMPLIES WITH THE ELECTRICAL SYSTEM AND EQUIPMENT REQUIREMENTS OF THE NORTH CAROLINA ENERGY CODE 2012, CHAPTER 5.	
SIGNED: _____	
NAME: TODD W. CAREY, P.E.	
TITLE: GEORGIA PROFESSIONAL ENGINEER #016927	

LABEL	TYPE OF FIXTURE	FINISH	LENS TYPE	VOLTAGE	LAMP	MANUFACTURER & MODEL NO.	REMARKS
A	RECESSED 2'x4' TROFFER	WHITE	PRISMATIC	120	(2) LED T8 BULBS	LITHONIA 2SP8G-332-FWA12-MVOLT	W/ NEW LITETRONICS LED RETROFIT KIT
B	HIGH BAY LED	WHITE	ACRYLIC	120	146W	LITHONIA IBH-18000LM-SD080-MD-MVOLT-0210-40K-80CRI-WGX-WH	XPW DIMMING RELAY
C	RECESSED 2'x4' SURFACE MTD	WHITE		120	(2) LED T8 BULBS	LITHONIA 2M 232 A12 MVOLT	W/ NEW LITETRONICS LED RETROFIT KIT
D	8' STRIP LIGHT	WHITE		120	(4) LED T8 BULBS	LITHONIA C-432-MVOLT	W/ NEW LITETRONICS LED RETROFIT KIT
EM	EMERGENCY EGGS	WHITE		120	INCLUDED	LITHONIA ELM2 LED	W/ BATTERY BACKUP
EX1	EXIT SIGN w/ REM HEAD	WHITE		120	INCLUDED	LITHONIA LHQM-LED	W/ MODEL ELALEDTP Dual Remote Head. 90 MIN BATTERY
EX	EXIT SIGN	WHITE	RED	120	INCLUDED	LITHONIA LQM S W 3 R 120/277 ELN	W/ BATTERY BACKUP
F	6' DOWNLIGHT LED	SPECULAR	CLEAR	120	18W	LITHONIA LDN6-35/10-L06AR-120-OS	
G	VANITY LED	NICKEL	ACRYLIC	120	18W	LITHONIA FMVTSL-24IN-MVOLT-30K-90CRI-BN	
H	4' STRIP LIGHT	WHITE		120	(2) LED T8 BULBS	LITHONIA C-232-MVOLT	W/ NEW LITETRONICS LED RETROFIT KIT
K	5" LED DOWNLIGHT	WHITE	CLEAR	120	11W	LITHONIA 5BPMW-LED-LSLEDT24	
L	WALL PACK LED	BRONZE	ACRYLIC	120	32W	LITHONIA OLW-23	PHOTOCELL



1 FIRST FLOOR PLAN - LIGHTING
SCALE: 1/8"=1'-0"






3 DUCT SMOKE DETECTOR WIRING
NO SCALE

2 ELECTRICAL SERVICE RISER
NO SCALE

ELECTRICAL NOTES:

1. GENERAL: ALL WORK SHALL CONFORM TO THE LATEST APPROVED EDITION OF THE NATIONAL ELECTRICAL CODE (NEC) AND ALL LOCAL JURISDICTIONAL CODES.
2. SCOPE: EXCEPT WHERE OTHERWISE SPECIFICALLY INDICATED ON THE DRAWINGS BY "FUTURE", "BY OTHERS", OR BY A SIMILAR NOTATION, IT IS THE INTENT THAT THE CONTRACTOR SHALL PROVIDE ALL MATERIALS, EQUIPMENT AND TOOLS NECESSARY TO PROVIDE ALL SYSTEMS IN COMPLETE AND OPERATING CONDITION.
3. EXCAVATE AS NECESSARY FOR THE INSTALLATION OF ELECTRICAL MATERIALS AND EQUIPMENT. VERIFY THE LOCATIONS OF EXISTING UNDERGROUND UTILITIES OR STRUCTURES BEFORE EXCAVATING AND EXERCISE CARE TO AVOID DAMAGE TO SUCH ITEMS DURING EXCAVATION. DUGGINGS, EXCAVATIONS, AND PITS SHALL BE FREE OF STONES AND FOREIGN DEBRIS, DEPOSITED IN 6" LAYERS AND COMPACTED TO A DENSITY OF NOT LESS THAN THAT OF THE SURROUNDING UNDISTURBED MATERIAL.
4. MATERIALS: THE MATERIALS AND EQUIPMENT FURNISHED SHALL BE AS INDICATED ON THE DRAWINGS; SUBSTITUTIONS SHALL NOT BE MADE EXCEPT WHERE EXPRESSLY APPROVED BY THE OWNER OR HIS REPRESENTATIVE PRIOR TO CONSTRUCTION. THE CONTRACTOR SHALL MAKE SURE ALL ELECTRICAL MATERIALS AND EQUIPMENT FURNISHED SHALL BE LISTED OR LABELED BY UNDERWRITERS LABORATORIES OR OTHER RECOGNIZED TESTING ORGANIZATION AND SHALL BE ACCEPTABLE TO THE LOCAL BUILDING AUTHORITY.
5. GROUNDING: GROUNDING SHALL BE IN ACCORDANCE WITH ARTICLE 250, NEC.
6. SHARED NEUTRAL CONDUCTORS SHALL NOT BE ALLOWED UNLESS INSTALLED IN ACCORDANCE WITH NEC-210.4
7. CONDUITS: PROVIDE CONDUITS WHERE CALLED FOR ON PANEL SCHEDULES; ELECTRICAL METALLIC TUBING (EMT) SHALL BE INSTALLED ONLY IN DRY LOCATIONS, IN CONCRETE ABOVE GRADE AND NOT SUBJECT TO PHYSICAL DAMAGE.
8. CONDUITS INSTALLED UNDERGROUND SHALL BE POLYVINYLCHLORIDE (PVC) AND SHALL NOT BE SMALLER THAN 3/4" TRADE SIZE, WHERE PVC CONDUIT IS INSTALLED UNDERGROUND, ELBOWS TURNING UP AND CONDUIT EMERGING ABOVE GRADE SHALL BE RSC. THE TOP OF CONDUITS SHALL BE PROTECTED BY A 1/2" SLEEVE, FINISHED IN PVC CONDUIT INSTALLED ABOVE GRADE OR DIRECT-BURIED IN EARTH SHALL BE NEMA TC2 TYPE EPC-40-PVC (SCHEDULE 40) EXCEPT THAT WHERE AREAS SUBJECT TO HEAVY VEHICULAR TRAFFIC, IT SHALL BE NEMA TC2 TYPE EPC-80-PVC (SCHEDULE 80).
9. CONDUCTORS: CONDUCTORS SHALL BE AS SCHEDULED ON PANEL SCHEDULES; ALL POWER CONDUCTORS SHALL NOT BE SMALLER THAN #10 AWG OR #12 AWG (ALUMINUM). CONTROL CONDUCTORS SHALL NOT BE SMALLER THAN #18 AWG CU.
10. CONDUCTORS SHALL BE CONTINUOUS FROM OUTLET TO OUTLET WITHOUT SPLICES EXCEPT WITHIN WIREWAY JUNCTION BOXES. MARK CONDUCTORS IN PANELS, PULL BOXES OR WIREWAYS AND TERMINAL STRIP TERMINALS FOR IDENTIFICATION OF CIRCUITS.
11. CONDUCTORS SHALL BE JOINED USING COMPRESSION SPLICES, EXCEPT THAT CONDUCTORS #10 AND SMALLER MAY BE JOINED USING WIRE NUTS. THE CONTRACTOR SHALL BE TERMINATED USING COMPRESSION OR PRESSURE TYPE TERMINAL LUGS, OR IN PRESSURE TERMINALS. COMPRESSION SPLICES USED ON CONDUCTORS #10 AWG AND SMALLER, SHALL BE THE SELF-INSULATED TYPE. INSULATED SPLICES SHALL BE INSTALLED USING 3M #334- OR #862- PLASTIC TAPE SPLICES IN WET LOCATIONS SHALL BE INSULATED WITH ELECTRICAL TAPE AND ENCAPSULATED WITH SCOTCHCAST OR EQUIVALENT POTTING COMPOUND.
12. PROVIDE AND INSTALL JUNCTION AND PULL BOXES WHERE INDICATED AND WHERE NECESSARY TO TERMINATE, TAP OFF, OR REDIRECT MULTIPLE CONDUIT RUNS, OF SIZE INDICATED OR AS REQUIRED BY NEC. WHERE FEEDER SPLICES ARE TO BE MADE, INSTALL BOXES LARGE ENOUGH TO PROVIDE AMPLE WORK SPACE.
13. LIGHTING FIXTURES: LIGHTING FIXTURES SHALL BE AS INDICATED ON THE DRAWINGS, AND SHALL BE INSTALLED COMPLETE WITH LAMPS. FIXTURES WITH ADJUSTMENTS AFFECTING LIGHT DISTRIBUTION SHALL BE SET TO PROVIDE THE REQUIRED LIGHT PATTERNS PRIOR TO THE FINAL DEMONSTRATION TEST.
14. TESTS: AFTER EACH SYSTEM HAS BEEN COMPLETED, A FUNCTIONAL TEST SHALL BE PERFORMED TO DEMONSTRATE THAT THE SYSTEM OPERATES IN ACCORDANCE WITH THE REQUIREMENTS OF THE DRAWINGS. THE TEST SHALL BE PERFORMED BY THE CONTRACTOR IN THE PRESENCE OF THE OWNER OR HIS REPRESENTATIVE.
15. TERMINALS: ALL ELECTRICAL EQUIPMENT FURNISHED ON THIS PROJECT IS TO HAVE TERMINALS RATED FOR 75 C. OPERATION.



1 FIRST FLOOR PLAN - POWER
SCALE: 1/8"=1'-0"

PANEL SCHEDULE C																
NEW PANELBOARD																
WIRE AND CONDUIT				LOAD DESCRIPTION		NEUT.	LINE A	LINE B	LINE C	LOAD DESCRIPTION						
##	BKR.	COND.	NEUTRAL	GND	C.	KEYS				KEYS	C.	GND	NEUTRAL	COND.	BKR.	##
1							0	2082							2	
3 35/3	#12	---	#12	1/2	CHAL	CONDENSING UNIT #1	0	1788								
5							0	2082							6	
7 20/1	#12	#12	#12	1/2	CHAL	AIR HANDLING UNIT #1	1920	1920								8
9							0	2082								
11 35/3	#12	---	#12	1/2	CHAL	CONDENSING UNIT #2	180	180								10
13							0	2082								
15 20/1	#12	#12	#12	1/2	CHAL	AIR HANDLING UNIT #2	1920	1920								14
							0	0								16
WIRE/CONDUIT KEY												PEAK PHASE (A) UNBALANCED NEUTRAL LOAD AMPS = 32.1 AMPS				
1234												NON DIVERSIFIED LOAD AT 208 VOLT, THREE PHASE = 66.1 AMPS				
11-TEMP RATING												PRINTED ON PANELS PROGRAM SERIAL NUMBER 2001.4001				
12-CONDUT TYPE												REGISTERED TO - TODD W. CAREY AND ASSOCIATES				
13-INSULATION																
14-WIRING TYPE																


PANEL C DIVERSIFICATION CALCULATIONS

RECEPTACLES (1) - 180 VA TOTAL
FIRST 10 KVA AT 100% - 180
HVAC LOAD AT 100% - 23616
PLUS 25% OF THE LARGEST MOTOR - 1431
TOTAL DIVERSIFIED PANEL LOAD - 28227
LOAD AT 120/208V/3-PHASE/4-WIRE - 70.1A

PANEL SCHEDULE 1C																
NEW PANELBOARD																
WIRE AND CONDUIT				LOAD DESCRIPTION		NEUT.	LINE A	LINE B	LINE C	LOAD DESCRIPTION						
##	BKR.	COND.	NEUTRAL	GND	C.	KEYS				KEYS	C.	GND	NEUTRAL	COND.	BKR.	##
1							0	3732							2	
3 50/3	#8	---	#10	3/4	CHAL	A/C UNIT #4	0	7716								4
5							0	3732								6
7 20/1	#12	#12	#12	1/2	CHAL	SERVICE RECEPTACLE	180	180								8
9							0	7716								10
11							0	7716								12
13							0	0								14
15							0	0								16
WIRE/CONDUIT KEY												PEAK PHASE (A) UNBALANCED NEUTRAL LOAD AMPS = 1.5 AMPS				
1234												NON DIVERSIFIED LOAD AT 208 VOLT, THREE PHASE = 160.2 AMPS				
11-TEMP RATING												PRINTED ON PANELS PROGRAM SERIAL NUMBER 2001.4001				
12-CONDUT TYPE												REGISTERED TO - TODD W. CAREY AND ASSOCIATES				
13-INSULATION																
14-WIRING TYPE																

PANEL IC DIVERSIFICATION CALCULATIONS

RECEPTACLES (1) - 180 VA TOTAL
FIRST 10 KVA AT 100% - 180
HVAC LOAD AT 100% - 57492
PLUS 25% OF THE LARGEST MOTOR - 2016
TOTAL DIVERSIFIED PANEL LOAD - 59688
LOAD AT 120/208V/3-PHASE/4-WIRE - 165.8A



PANEL SCHEDULE B																
RELOCATED EXTG PANELBOARD																
WIRE AND CONDUIT				LOAD DESCRIPTION		NEUT.	LINE A	LINE B	LINE C	LOAD DESCRIPTION						
##	BKR.	COND.	NEUTRAL	GND	C.	KEYS				KEYS	C.	GND	NEUTRAL	COND.	BKR.	##
1 15/1	#12	#12	#12	1/2	CHAL	POPCORN MACHINE	1800	1800		GYM LIGHTS	CHAL	1/2	#12	#12	20/1	2
3 15/1	#12	#12	#12	1/2	CHAL	DRINK REFRIGERATOR	499	499		GYM LIGHTS	CHAL	1/2	#12	#12	20/1	4
5 15/1	#12	#12	#12	1/2	CHAL	NACHO CHIP WARMER	1752	1752		GYM LIGHTS	CHAL	1/2	#12	#12	20/1	6
7 15/1	#12	#12	#12	1/2	CHAL	HOTDOG MACHINE	1245	1245		GYM LIGHTS	CHAL	1/2	#12	#12	20/1	8
9 15/1	#12	#12	#12	1/2	CHAL	PRETZEL MACHINE	88	88		GYM LIGHTS	CHAL	1/2	#12	#12	20/1	10
11 15/1	#12	#12	#12	1/2	CHAL	CHEESE MACHINE	290	290		GYM LIGHTS	CHAL	1/2	#12	---	20/2	12
13 15/1	#12	#12	#12	1/2	CHAL	SNOW CONE MACHINE	840	840		INSTA-HOT WATER HEATER	CHAL	1/2	#12	---	20/2	14
15 15/1	#12	#12	#12	1/2	CHAL	UNDER COUNTER ICE MACHINE	1200	1200		INSTA-HOT WATER HEATER	CHAL	1/2	#12	---	20/2	16
17 15/1	#12	#12	#12	1/2	CHAL	UNDERCOUNTER REFRIGERATOR	396	396		INSTA-HOT WATER HEATER	CHAL	1/2	#12	---	20/2	18
19 20/1	#12	#12	#12	1/2	CHAL	OFFICE RECEPTACLE	540	540		INSTA-HOT WATER HEATER	CHAL	1/2	#12	---	20/2	20
21 20/1	#12	#12	#12	1/2	CHAL	MEETING/PARTY RECEPTACLE	720	720		MOTORIZED GOAL	CHAL	1/2	#12	#12	20/1	22
23 20/1	#12	#12	#12	1/2	CHAL	GYM RECEPTACLE	900	900		SCOREBOARD	CHAL	1/2				